



### Ordering data

6SE6440-2UD31-5DA1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		General tech. specifications	
<b>Input</b>		<b>Power factor <math>\lambda</math></b>	0.95
<b>Number of phases</b>	3 AC	<b>Efficiency <math>\eta</math></b>	0.96
<b>Line voltage</b>	380 ... 480 V $\pm 10\%$	<b>Ambient conditions</b>	
<b>Line frequency</b>	47 ... 63 Hz	<b>Cooling</b>	Fan
<b>Rated current (LO)</b>	37.00 A	<b>Ambient temperature</b>	
<b>Rated current (HO)</b>	33.80 A	<b>Operation (LO)</b>	-10 ... 40 °C
<b>Output</b>		<b>Operation (HO)</b>	-10 ... 50 °C
<b>Number of phases</b>	3 AC	<b>Transport</b>	-40 ... 70 °C
<b>Rated voltage</b>	480 V	<b>Storage</b>	-40 ... 70 °C
<b>Rated power (LO)</b>	18.50 kW / 25.00 hp		
<b>Rated power (HO)</b>	15.00 kW / 20.00 hp		
<b>Rated current (LO)</b>	38.00 A		
<b>Rated current (HO)</b>	32.00 A		
<b>Pulse frequency</b>	4000 Hz		
<b>Output frequency for V/f control</b>	0 ... 650 Hz		

Due to legal restrictions a limitation to 550 Hz is under preparation

### Overload capability

#### Low Overload (LO)

140 % output current for 3 s, followed by 110 % output current for 57 s followed by 100 % output current for 240 s in a 300 s cycle time

#### High Overload (HO)

150 % output current for 60 s, followed by 100 % output current for 240 s in a 300 s cycle time



Ordering data

6SE6440-2UD31-5DA1

### Mechanical data

Degree of protection	IP20
Size	D
Net weight	16.00 kg
Width	275.0 mm
Height	520.0 mm
Depth	245.0 mm

### Connections

#### Motor end

Conductor cross-section	35.00 mm <sup>2</sup>
-------------------------	-----------------------

### Inputs/ outputs

#### Standard digital inputs

Number	6
--------	---

#### Relay output

Number	3
--------	---

#### Analog inputs

Number	2
--------	---

#### Analog outputs

Number	2
--------	---

#### PTC/ KTY interface

Number	1
--------	---