



Ordering data

6SL3224-0BE24-0UA0

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Rated data

Input

Number of phases	3 AC
Line voltage	380 ... 480 V $\pm 10\%$
Line frequency	47 ... 63 Hz
Rated current with line reactor	10.40 A
Rated current without line reactor	13.40 A

Output

Number of phases	3 AC
Rated voltage	400 V
Rated power (LO)	4.00 kW
Rated power (HO)	4.00 kW
Rated current (LO)	10.20 A
Rated current (HO)	10.20 A
Max. output current	20.40 A
Pulse frequency	4 kHz
Output frequency for vector control	0 ... 200 Hz
Output frequency for V/f control	0 ... 550 Hz

General tech. specifications

Power factor λ	0.85
Offset factor $\cos \varphi$	0.95
Efficiency η	0.95
Sound pressure level (1m)	50 dB
Power loss	0.18 kW

Ambient conditions

Cooling	Internal air cooling
Cooling air requirement	0.024 m ³ /s
Installation altitude	1000 m
Ambient temperature	
Operation LO	0 ... 40 °C (32 ... 104 °F)
Operation HO	0 ... 50 °C (32 ... 122 °F)
Transport	-40 ... 70 °C (-40 ... 158 °F)
Storage	-25 ... 55 °C (-13 ... 131 °F)

Relative humidity

Max. operation	95 % RH, condensation not permitted
----------------	-------------------------------------

Overload capability

Low Overload (LO)

1.1 × output current rating (i.e., 110 % overload) for 57 s with a cycle time of 300 s
1.5 × output current rating (i.e., 150 % overload) for 3 s with a cycle time of 300 s

High Overload (HO)

1.5 × output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s
2 × output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s



Ordering data

6SL3224-0BE24-0UA0

Mechanical data

Degree of protection	IP20
Size	FSB
Net weight	4.00 kg
Width	153.0 mm
Height	270.0 mm
Depth	165.0 mm

Connections

Line side

Version	Screw-type terminals
Conductor cross-section	1.00 ... 6.00 mm ²

Motor end

Version	Screw-type terminals
Conductor cross-section	1.00 ... 6.00 mm ²

DC link (for braking resistor)

Conductor cross-section	1.00 ... 6.00 mm ²
-------------------------	-------------------------------

Max. motor cable length

Shielded	50 m
Unshielded	100 m

Standards

Compliance with standards	UL, cUL, CE, C-Tick, SEMI F47
CE marking	According to low-voltage directive 2006/95/EC